



WASHING

NORMAL SPIN WASHERS LOW AND MEDIUM CAPACITY FWS-40 TP2



FEATURES

Touch Plus Control

- 7" touchscreen, user friendly and totally programmable.
- Videos on display, ads, instructions.
- Free software for programming, telemetry, data analysis.
- USB Connection.
- 37 Languages.
- 8 dosing signals.

G FACTOR

- G-FACTOR 200.

EFFICIENCY

- Energy Optimization.
- Optimal load.
- Low water consumption.

VERSATILITY

- Custom- Make to order.
- OPL or COIN.
- Electric or Hot water.
- Wet cleaning features.

CONNECTIVITY

- IoT - Fagor-Konnect standard.
- Remote technical service.
- Laundry Management system: OPL and COIN.

ERGONOMICS

- Large Loading doors: Ø460.
- Easy opening/closing system for door lock.

MAINTENANCE

- Hinged panel: easy access to parts.
- Equivalent parts for all models: contactors, electronic devices, gear.
- Technical menu: traceability, error diagnosis.

OTHERS


- Hard mounted washers.
- Anchoring to floor with anchoring base.
- Panels in skin plate.
- 3 water inlets.
- CB and WRAS approved.

OPTIONS

- Extra dosing pump DB-1.
- Anchoring base.
- Double drain.
- Relay card with 6 extra dosing signals.
- Silicone gasket.
- Reversible door opening.
- Tropicalized coating.
- Stainless steel AISI 304 outer casing.
- Stainless steel AISI 304 front panel.
- Coin / token kit.
- Auto unlock kit for the door.

DRUM		
	U.	FWS - 40 TP2
Load capacity 1:9 / 1:10	Lb.	44.1/39.7
Volume	CU.FT	6.5
Diameter	In	27.6
Depth	In	18.5
GENERAL DETAILS		
Washing speed / Spinning speed	r.p.m.	50/714
G Factor	-	200
Maximum force transmitted	KN	2.63 ±5
Frequency-dynamic force	Hz	8.42
Noise level	dB	<70
Coin laundry version	-	Yes
Double drain	-	Opt.
Weighing System / Tilting System	-	No
SLUICE option	-	Yes
DOOR		
Height center door / Height door	In	25.8/13.7
Diameter	In	18.1
POWER		
Motor	Hp	3
Electric heating power	kW	12
Total electric power (electric model)	kW	12.75
Total electric power (hw, steam model)	kW	2.2
CONNECTIONS		
Voltage 208-240/60/1~ + G	Nº x AWG / A	3 x 10 / 70A
Voltage 208-240/60/3~ + G	Nº x AWG / A	4 x 8 / 40A
Voltage 440-480/3 ~ + G	Nº x AWG / A	4 x 10 / 30A
Steam inlet (Steam model)	inch	1/2"
Maximum steam consumption (Steam model)	lbs/h	12
Water inlet	inch	3/4"
Water main pressure	Kg/cm2	2-4
Maximum water consumption	Gal/h	31.7*
Drain	mm/inch	3"
Drainage capacity	Gal/min	52.8
DIMENSIONS / PACKING DIMENSIONS		
Net Width / Gross Width	In	31.02/33.5
Net Depth / Gross Depth	In	36.81/39.9
Net Height / Gross Height	In	51.46/62.4
Net weight / Gross weight	Lbs.	599.8/681.3
Volume	Ft3	48

* Programmed No. 20, 75% load



		A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	CGY	CGZ
FWS - 40	mm	788	935	1307	348	460	143	552	1035	1203	1038	1222	1107	61	74	101	385	445	706	544	245	724	676	1202	485	1202	479	546
	In	31.02	36.81	51.46	13.70	18.11	5.63	21.73	40.75	47.36	40.87	48.11	43.58	2.40	2.91	3.98	15.16	17.52	27.80	21.42	9.65	28.50	26.61	47.32	19.09	47.32	18.86	21.50